



3915 152ND ST NE | MARYSVILLE, WA 98271 | 1.800.827.3747

**Product Overview**

The Narkomed GS incorporates state-of-the-art electronics combined with a user friendly interface that claims extremely intuitive controls. The machine is equipped with a single monitor screen which provides volume, pressure and oxygen data. All monitored parameters and alarm messages are displayed on a bright, easy to read EL display.

The Narkomed GS is equipped with the AV2 which is a volume preset, time cycled and pressure limited ventilator. It is equipped with electronic timing, pneumatic circuitry and independent controls for frequency, I:E ratio, inspiratory flow rate, tidal volume and inspiratory pressure limit. The unit is also equipped with a back up battery that will operate the ventilator for a full 30 minutes.



**DRÄGER® NARKOMED GS**

**Specifications:**

**Dimensions:**

Height: ..... 53 inches  
 Width: ..... 36 inches  
 Depth: ..... 27 inches  
 Weight: ..... 375 lb

**Power Input:**...120 VAC, 60Hz, 220-240 VAC 50Hz

**Oxygen Monitoring**

Range .....10 – 100%  
 Resolution.....1 vol %  
 Accuracy..... ± 3 vol %

**Airway Pressure Monitoring**

Range ..... -10 – 125 cmH2O  
 Resolution.....1 cmH2O

**Accuracy:**..... ± 3 cmH2O or ± 10% of reading  
 whichever is higher

**Tidal Volume Monitoring**

Range.....0.2 – 50 L  
 Resolution..... 0.1 L  
 Accuracy.....10% or 0.1 L, whichever is higher

**Ventilator**

Frequency (breaths per minute).....1 – 99  
 I:E Ratio.....4:1 – 1:4.5  
 Inspiratory Flow.....10 – 100 l/min  
 Tidal Volume.....50 – 1,500 ml